

IOMod Modbus RTU Slave firmware change-log

Elseta IOMod series devices support's **Modbus RTU** Slave protocol.



This firmware can be used for IOMod series devices: IOMod 8DI8DO v1.x, IOMod 16DI v1.x, IOMod 8AI v1.x, IOMod 4RTD v1.x, IOMod HT v1.x



This version does not support IOMod 4Cs4Vs model.

Firmware	Version	Release Date	Changes
IOMOD_MODBUS_v1_21_0.bin	1.21	2023-07-26	<ul style="list-style-type: none">added 8DI4RO support
IOMOD_MODBUS_v1_19.bin	v1.19	2020-07-01	<ul style="list-style-type: none">Fixed SPI readings for IOMod 8AI by lowering SPI clock speed to 400kHz
IOMOD_MODBUS_v1_18.bin	v1.18	2019-08-23	<ul style="list-style-type: none">Fixed crash introduced by a higher range of temperatures (>40 C)
IOMOD_MODBUS_v1_17.bin	v1.7.3	2019-01-30	<ul style="list-style-type: none">Fixed possible race condition where two or more inputs change at once and stop IOMod device from calculating input calculations further. Inputs are now polled every 1 ms.

🕒Revision #3

★Created 10 November 2021 16:34:58 by Raimundas Slavinskas

✎Updated 3 August 2023 10:44:25 by Tomas