

# 21 MQTT

## Introduction

MQTT (short for MQ Telemetry Transport) is an open OASIS and ISO standard (ISO/IEC PRF 20922) lightweight, publish-subscribe network protocol that transports messages between devices. The protocol usually runs over TCP/IP, although its variant, MQTT-SN, is used over other transports such as UDP or Bluetooth. It is designed for connections with remote locations where a small code footprint is required or the network bandwidth is limited.

The broker acts as a post office, MQTT doesn't use the address of the intended recipient but uses the subject line called "Topic", and anyone who wants a copy of that message will subscribe to that topic. Multiple clients can receive the message from a single broker (one to many capability). Similarly, multiple publishers can publish topics to a single subscriber (many to one).

Each client can both produce and receive data by both publishing and subscribing, i.e. the devices can publish sensor data and still be able to receive the configuration information or control commands. This helps in both sharing data, managing and controlling devices.

With MQTT broker architecture the devices and application becomes decoupled and more secure. MQTT might use Transport Layer Security (TLS) encryption with user name, password protected connections, and optional certifications that requires clients to provide a certificate file that matches with the server's. The clients are unaware of each others IP address.

The broker can store the data in the form of retained messages so that new subscribers to the topic can get the last value straight away.

The main advantages of MQTT broker are:

- Eliminates vulnerable and insecure client connections
- Can easily scale from a single device to thousands
- Manages and tracks all client connection states, including security credentials and certificates
- Reduced network strain without compromising the security (cellular or satellite network)

Each connection to the broker can specify a quality of service measure. These are classified in increasing order of overhead:

- At most once - the message is sent only once and the client and broker take no additional steps to acknowledge delivery (fire and forget).
- At least once - the message is re-tried by the sender multiple times until acknowledgement is received (acknowledged delivery).
- Exactly once - the sender and receiver engage in a two-level handshake to ensure only one copy of the message is received (assured delivery).

## Using WCC Lite as MQTT Client

MQTT serves as an alternative for protocols conforming to IEC standards, for example, to send data to a cloud infrastructure that supports MQTT instead of IEC-60870-5-104.

✔ WCC Lite supports MQTT messaging compatible with MQTT v3.1 standard (starting from version **v1.4.0**). Such messaging is possible via mapping of Redis and MQTT data therefore data can be transmitted from any protocol that is supported by WCC Lite.

All standard functions, except for data encryption, are supported. Encrypted messages are not supported yet, therefore to ensure security a user would have to use a VPN service. A user can choose from three different Quality of Service levels, select if messages are to be retained, authenticate users and optionally send Last Will messages.

To configure WCC Lite a user can fill in the needed parameters in Excel configuration. These parameters are shown in the two tables below.

Table. MQTT parameters for Devices tab

Parameter	Type	Description	Required	Default value (when not specified)	Range	
					Min	Max

name	string	User-friendly device name	Yes			
device_alias	string	Device alias to be used in the configuration	Yes			
enable	boolean	Enabling/disabling of a device	No	0	0	1
protocol	string	Selection of protocol	Yes		MQTT	
ip	string	MQTT broker IP address selection	Yes			
port	integer	MQTT broker port selection	No	1883		
enable_threshold	boolean	A parameter to determine if identical values should not be sent multiple times in a row.	No	1	0	1
gi_interval_sec	integer	Parameter to determine how frequently should all values be sent at once. Disabled if equal to 0.	No	0		
mqtt_qos	integer	MQTT Quality of Service for message as in standard	No	0	0	2
mqtt_retain	boolean	Selecting if MQTT broker should retain last received messages	No	0	0	1
user	string	MQTT user name	Yes			
password	string	MQTT user password	Yes			
use_last_will	boolean	Selecting if MQTT should use Last Will and Testament functionality (Default: False)	No	0	0	1
last_will_topic	string	Topic to which an MQTT message would be sent if the device abruptly disconnected message broker	Yes (If use_last_will=True)			
last_will_message	string	Message to be sent over MQTT if the device abruptly disconnected message broker	No			
last_will_qos	integer	MQTT Quality of Service selection as in standard	No	0		
last_will_retain	boolean	Selecting if MQTT broker should retain last will message	No	0	0	1

To map the signal to send through MQTT client, it should have its device\_alias and signal\_alias mapped to source\_device\_alias and source\_signal\_alias respectively.

If MQTT is configured but does not send data, a user can use command line interface to debug transmission. All options for MQTT process which transmits data over MQTT (called mqtt-client as it

Table. MQTT parameters for Signals tab

Parameter	Type	Description	Required	Default value (when not specified)	Range	
					Min	Max
signal_name	string	User-friendly signal name	Yes			
device_alias	string	Device alias from a Devices tab	Yes			
signal_alias	string	Unique signal name to be used	Yes			
source_device_alias	string	device_alias of a source device	No			
source_signal_aliases	string	signal_alias of a source signal	No			
enable	boolean	Enabling/disabling of an individual signal	No	1	0	1
log	integer	Allow signal to be logged. Log signal with 1 and no logging with 0.	No	0		
topic	string	Topic name to override the value built by default	No			

## MQTT data format

The format of a MQTT message is a bit different than Redis messages. Redis messages are supported as CSV strings: value,timeStamp,flags (where value can be float, integer or nan; timeStamp - Unix timestamp in milliseconds; flags contain additional information about a measurement). MQTT messages are supported as value,timestamp,quality (where value can be float, integer or nan; timeStamp - Unix timestamp in milliseconds; quality shows if a value is to be considered as valid). Quality parts of a string is always equal to 1 except for Redis messages containing invalid (IV), non-topic (NT) and/or overflow (OV) flags.

As mentioned, MQTT client acts as an adapter between Redis and MQTT, therefore data from topic in Redis is written to a topic in MQTT. Therefore mqtt-client has to know the mapping table before starting. This table is saved at /etc/elseta-mqtt.json. Every Redis topic name is constructed as tag/[device\_alias]/[signal\_alias]/[direction]. Prefix tag/ is always used before the rest of argument. `device_alias` and `signal_alias` represent columns in Excel configuration. Direction can have one of four possible values - rout, out, in, rin; all of which depend on the direction data is sent or acquired protocol-wise. The same Redis topic structure is preserved in MQTT by default making it easier to find matching signals, however, as no recalculation is done by MQTT and only PUBLISH messages are now supported, only Redis signals with in direction have their MQTT mappings.

A user can create and select his own topic name in Excel configuration, in topic column. As no recalculation is done by MQTT and only PUBLISH messages are now supported, only Redis signals with in direction have their MQTT mappings.

## Debugging a MQTT protocol

If configuration for MQTT is set up, handler for protocol will start automatically. If configuration is missing or contains errors, protocol will not start. It is done intentionally to decrease unnecessary memory usage.

MQTT Client command line debugging options

`mqtt-client`

```
-h [ -help ] Display help information
-c [ -config ] Configuration file location (default - /etc/elseta-mqtt.conf)
-V [ -version ] Show version
-d<debug level> [ -debug ] Set debugging level
-r [ -redis ] Show REDIS output
-m [ -mqtt ] Show MQTT output
```



If MQTT Client does not work properly (e.g. no communication between devices, data is corrupted, etc.), a user can launch a debug session from command line interface and find out why link is not functioning properly.



To launch a debugging session, a user should stop `mqtt-client` process and run `mqtt-client` command with respective flags as was shown above.

---

🔄Revision #4

★Created 18 March 2022 09:52:10 by Tautvilis

✎Updated 29 March 2022 14:25:55