

Documentation

WCCLite manual for version 1.11.0

Manual --> [Download](#)

WCCLite manual for version 1.10.0

Manual --> [Download](#)

WCCLite manual for version 1.9.3

Manual --> [Download](#)

WCCLite manual for version 1.9.0

Manual --> [Download](#)

WCCLite+ manual for version 1.1.18

Manual --> [Download](#)

WCCLite manual for version 1.8.3

Manual --> [Download](#)

WCCLite+ manual for version 1.1.3

Manual -> [Download](#)

WCCLite manual for version 1.6.3

Manual -> [Download](#)

WCCLite manual for version 1.6.2

Manual -> [Download](#)

WCCLite manual for version 1.5.4 (released 27/08/2021)

Manual -> [Download](#)

General



WCC Lite
mini RTU & gateway

WCC Lite is a single-box device not require any vendor-specific power supply or other components and can work as a standalone device for applications such as protocol converting, mini RTU without I/Os, datalogger, etc. WCC Lite is ideal for retrofit projects – as its small footprint allows to fit it into any existing cabinet, while its wide variety of supported protocols and possibility for converting them to each other gives a perfect fit. Additional DI and relay outputs allow to send information to the SCADA system about error-rates and indicate errors on cabinet door status, a simple single command.

Due to the integrated features, WCC Lite with the integrated 4G/LTE module allows to switch from existing radio infrastructure to mobile coverage. WCC Lite has an ideal set of features to be a perfect choice for small sites including 4G/LTE, and VPN features. The high bandwidth of 4G/LTE allows to integrate of video surveillance (SD) remote access for configuration, COMFINDER and other needs.

Applications

- Power Grid
- Solar energy projects
- Wind energy projects
- Hydro energy projects
- Energy storage applications
- Factory resources supervision
- Substation automation solutions

Features

- Protocol converter
- Data logger
- Industrial grade router and Ethernet switch
- Rule-based Firewall
- Mobile connectivity via integrated 4G/LTE, 3G modem with dual SIM card support
- VPN client and server (PPTP and OpenVPN)
- Web-based configuration
- Remote Authentication Dial-In User Service (RADIUS)
- Cybersecurity
 - IEEE 1588-2007
 - WEB SSL support for configuration
 - DoS, spoofing prevention
 - ICMP, Multicast, VPN filtering
 - IPsec
 - RADIUS

Copyright © 2015 Elseta Ltd.
www.elseta.com

Page 1

WCC Lite

CE -> [Download](#)

ISO 9001 -> [Download](#)

Step file -> [Download](#)

PID's

IEC-60870-5-103 -> [Download](#)

IEC-60870-5-104 -> [Download](#)

IEC-60870-5-101-Slave -> [Download](#)

IEC-60870-5-101-Master -> [Download](#)

🕒Revision #32

★Created 27 December 2021 10:32:27

✍Updated 21 March 2025 14:43:06 by Gabriele